



# SAFETY DATA SHEET

## STATEMENT OF HAZARDOUS NATURE

This product is classified as not hazardous.

## COMPANY DETAILS

**SUPPLIER NAME:** Golden West Lubricants  
**ADDRESS:** 30 Wildfire Rd  
Maddington WA6109  
**Tel:** (08) 9452 3422  
**TELEPHONE NUMBER:** (02) 289 9789  
**EMERGENCY TELEPHONE NUMBER:** (02) 289 9789 (Technical Dept)

## IDENTIFICATION

**PRODUCT NAME:** LITH-PLEX RGM-2  
**OTHER NAMES:** None.  
**MANUFACTURER'S PRODUCT CODE:** 5042302  
**UN NUMBER:** Not applicable.  
**HAZCHEM CODE:** Not applicable.  
**DANGEROUS GOODS CLASS/SUBSIDIARY RISK:** Not applicable.  
**POISONS SCHEDULE NUMBER:** Not applicable.

## USE

High temperature, extreme pressure, multiservice grease for use in automotive and industrial applications.

## PHYSICAL DESCRIPTION/PROPERTIES

**APPEARANCE:** Smooth black grease.  
**VAPOUR PRESSURE(Pa or mmHg at 20°C):** Not available.  
**DENSITY @ 15°C (g/mL):** Typically 0.9.  
**FLASHPOINT(°C):** >200°C(ASTM D-93).  
**FLAMMABILITY LIMITS(%):** Not available.  
**SOLUBILITY IN WATER(g/L):** Not miscible with water.

## OTHER PROPERTIES

**BOILING POINT (°C):** > 316 °C.  
**DROP POINT (°C):** > 260 °C.  
**VISCOSITY @ 40 °C(cSt):** Typically 460.  
**PENETRATION, UNWORKED:** Typically 280.

## IDENTIFICATION continued

## **INGREDIENTS**

| CHEMICAL ENTITY:   | CAS No.    | PROPORTION |
|--|------------|------------|
| Residual Oils(Petroleum), Solvent Dewaxed                    | 64742-62-7 | > 60%      |
| Distillates(Petroleum), Solvent Dewaxed Light Naphthenic     | 64742-64-9 | < 10%      |
| 12-Hydroxy Stearic Acid                                      | 8001-78-3  | < 10%      |
| Butene, Homopolymer  | 9003-29-6  | < 10%      |
| Mixture of Sulphur and Phosphorus Compounds                  | -          | < 10%      |
| Zinc Dialkyl Dithiophosphate                                 | 68649-42-3 | < 10%      |
| Borated Ester Complexing Agent                               | -          | < 10%      |
| Lithium Hydroxide Monohydrate                                | 1310-66-3  | < 10%      |
| Mixture of Octylated Diphenylamines                          | 68921-45-9 | < 10%      |
| Zinc Oxide   | 1314-13-2  | < 20%      |
| Graphite   | 7782-42-5  | < 20%      |
| Molybdenum Sulfide   | 1317-33-5  | < 10%      |
| 2-(2-Heptadec-8-enyl-2-imidazolin-1-yl) Ethanol              | 95-38-5    | < 10%      |
| Mixture of Alkyl Mercaptothiadiazoles                        | -          | < 10%      |
| Mixture of Polyolefin Additive in Highly Refined Mineral Oil | -          | < 10%      |

## **HEALTH HAZARD INFORMATION**

### **HEALTH EFFECTS**

|                          |                       |   |
|--------------------------|-----------------------|---|
| <i>ACUTE</i>             | SWALLOWED:            | This is not expected to be a means of entry during routine operation. Ingestion of small quantities should not cause irritation.  |
|                          | EYE:                  | May cause slight irritation to the eyes.  |
|                          | SKIN:                 | May be mildly irritating to the skin. High pressure injection through the skin, when using apparatus such as grease guns, can be highly irritating and may cause localised damage.  |
|                          | INHALED:              | No data to indicate a toxic inhalation hazard. Inhalation of vapours or mist (generated at elevated temperatures) may cause irritation to the nose and throat.  |
| <i>CHRONIC:</i>          |                       | Prolonged or repeated skin contact may lead to drying of the skin.  |
| <i>FIRST AID</i>         | SWALLOWED:            | If a large quantity is ingested seek medical attention. It may be necessary to induce vomiting, taking extreme care that the person does not aspirate into the lungs. If aspiration occurs, urgent medical attention should be sought.  |
|                          | EYE:                  | Wash with copious amounts of water for 15 minutes and seek medical advice if irritation develops or persists.   |
|                          | SKIN:                 | Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. High pressure injection through the skin requires urgent medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns(Do not remove material). |
|                          | INHALED:              | Remove person to fresh air and seek medical advice. If not breathing, apply artificial respiration and seek urgent medical aid.   |
|                          | FIRST AID FACILITIES: | Eye wash fountains and safety showers are recommended.  |
| <i>ADVICE TO DOCTOR:</i> |                       | Treat symptomatically.  |

## **PRECAUTIONS FOR USE**

|                       |  |
|-----------------------|--|
| EXPOSURE STANDARDS:   | If the material is subjected to high temperature operations and mists or vapours are generated the Manufacturer recommends:<br>Time Weighted Average (TWA): 5 mg/m <sup>3</sup> (oil mist).<br>Short Term Exposure Limit (STEL): 10 mg/m <sup>3</sup> (oil mist).  |
| ENGINEERING CONTROLS: | Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the |

manufacturer recommended exposure standard.

### **PERSONAL PROTECTION**

|                           |   |
|---------------------------|---|
| RESPIRATOR TYPE (AS1716): | During routine operation a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required.     |
| GLOVE TYPE:               | PVC, Neoprene or Nitrile gloves are recommended.  |
| EYE PROTECTION:           | Safety glasses or goggles are recommended to avoid eye contact. If the material is used at elevated temperatures or under pressure a full face shield should be worn. |
| CLOTHING:                 | During normal operating procedures, long sleeved clothing is recommended to provide skin protection. Soiled clothing should be washed with detergent prior to re-use. |

### **FLAMMABILITY**

|                             |  |
|-----------------------------|--|
| FIRE HAZARDS:               | Not flammable under conditions of use. Is a combustible solid that will burn if preheated. |
| SOURCES OF IGNITION ADVICE: | Not applicable.  |
| HAZCHEM CODE:               | Not applicable.  |

## **SAFE HANDLING INFORMATION**

|                        |   |
|------------------------|---|
| STORAGE AND TRANSPORT: | Classified as a combustible solid. Store in a well ventilated area away from ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Do not store in plastic containers unless approved for this application.  |
| SPILLS AND DISPOSAL:   | Spills are easily contained due to the nature of the product. Caution: The product may be slippery. The product should be shovelled into a metal drum and treated as a solid waste. Follow state or local regulations for the disposal of the waste. Clean area with soap and water. Do not allow product to enter drains, sewers or water courses – inform local authorities if this occurs. |

## **SAFE HANDLING INFORMATION continued**

### **FIRE/EXPLOSION HAZARD**

|   |   |
|---|---|
| HAZARDS OF USE/STORAGE:                                 | This product is combustible if preheated.   |
| LIST OF DANGEROUS DECOMPOSITION OR COMBUSTION PRODUCTS: | Combustion produces oxides of carbon, nitrogen, sulphur, phosphorus, molybdenum and zinc.     |
| FIRE-FIGHTING RECOMMENDATIONS:                          | Keep storage tanks, pipelines, containers, fire exposed surfaces, etc. cool with water spray. |
| TYPES OF EXTINGUISHER/<br>FIRE-FIGHTING AGENTS:         | Use foam, carbon dioxide or dry chemical.   |
| PRECAUTION:   | Water may cause splattering.  |
| PROTECTIVE CLOTHING:                                    | Self-contained breathing apparatus is recommended during a fire.                              |
| REACTIVITY:   | May react with strong oxidising agents.   |

## **OTHER INFORMATION**

### **TOXICOLOGICAL DATA:**

ORAL TOXICITY(RATS): Based upon testing of similar products and/or components, this material is considered to be relatively non-toxic with a LD50: > 2000 mg/Kg.

DERMAL TOXICITY(RABBITS): Based upon testing of similar products and/or components, this material is considered to be relatively non-toxic with a LD50: > 2000 mg/Kg.

EYE IRRITATION(RABBITS): Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Draize Score: Greater than 6, but less than 15.

SKIN IRRITATION(RABBITS): Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Primary Irritation Index: Greater than 0.5, but less than 3.

SUBCHRONIC TOXICITY(RATS): Based upon testing of similar products and/or components, this material is considered to show no adverse effects by dermal application to rats.

REPRODUCTIVE TOXICITY(RATS): Based upon testing of similar products and/or components, this material is considered to show no adverse effects in either the mothers or their offspring by dermal exposure of pregnant rats.

CHRONIC TOXICITY(MICE): Based upon testing of similar products and/or components, this material is considered to show no evidence of carcinogenic effects by chronic mouse skin painting studies.

SENSITISATION(GUINEA PIGS): Based upon testing of similar products and/or components, this material is considered to show no evidence of skin sensitisation to guinea pigs during studies.

## CONTACT POINT

TITLE: Technical Department Supervisor  
TELEPHONE NUMBER: (02) 289 9789

All information contained in this Material Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.